NSN 5930-01-245-4692

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-245-4692

Body Style:
Printed circuit
Overall Length:
0.480 inches
Overall Height:
0.500 inches
Overall Width:
0.405 inches
Body Length:
0.480 inches
Body Width:
Between 0.370 inches and 0.405 inches
Body Height:
Between 0.230 inches and 0.300 inches
Case Material:
Plastic
Switch Actuator Quantity:
4
Actuator Length:
Between 0.045 inches and 0.065 inches
Actuator Style:
Rectangular
Actuator Height:
0.040 inches
Actuator Width:
Between 0.055 inches and 0.085 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained
Maximum Voltage Rating In Volts:
6.0 dc and 24.0 dc
End Application:
5820-01-145-4901 control, orderwire
Mounting Method:
Printed circuit
Nonpile-up Contact Arrangement:
1 pole, single throw, both positions maintained 5th switch unit
Contact Load Current Rating At Maximum Rated Voltage:
100.0 milliamperes resistive dc and 25.0 milliamperes resistive dc
Precious Material And Location:
Contact surfaces gold
Test Data Document:
81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5930-01-245-4692

Slide Switch - Page 2 of 2



Terminal Type And Quantity:
8 printed circuit
Specification Data:
81349-mil-s-83504/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0