

View Online at <https://aerobasegroup.com/nsn/5930-01-245-6559>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Height:

0.690 inches

Body Height:

Between 0.350 inches and 0.405 inches

Overall Diameter:

Between 0.560 inches and 0.640 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Surface

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 500.0 milliamperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

250.00 actuation point degrees fahrenheit and 225.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-24236/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0