NSN 5930-01-245-6564

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-245-6564

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.346 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.740 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Natural single actuator
Actuator Inscription:
12 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.076 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and full display lens
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

NSN 5930-01-245-6564

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0