

View Online at <https://aerobasegroup.com/nsn/5930-01-245-9273>

Thread Class:

2a 2nd mounting facility

Thread Length:

0.410 inches 1st mounting facility

Overall Length:

3.279 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.365 inches

Nonturn Device Radius:

0.375 inches at 12: 00 o'clock

Distance Between Mounting Facility Centers:

0.888 inches 2nd mounting facility

Individual Section Quantity:

5

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Coded

Mounting Method:

Threaded stud 2nd mounting facility

Thready Qty Per Inch (tpi):

72 2nd mounting facility

Thread Size:

0.375 inches 1st mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

21 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

0.1 amperes resistive load dc at sea level

Contact Arrangement Truth Table:

Special each section

Special Truth Table Identification:

91812-code b 21 each section

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0