

View Online at <https://aerobasegroup.com/nsn/5930-01-245-9273>

**Thread Class:**

2a 2nd mounting facility

**Thread Length:**

0.410 inches 1st mounting facility

**Overall Length:**

3.279 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.437 inches single actuator

**Overall Diameter:**

1.365 inches

**Nonturn Device Radius:**

0.375 inches at 12: 00 o'clock

**Distance Between Mounting Facility Centers:**

0.888 inches 2nd mounting facility

**Individual Section Quantity:**

5

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Switch Contact Basic Design:**

Coded

**Mounting Method:**

Threaded stud 2nd mounting facility

**Thready Qty Per Inch (tpi):**

72 2nd mounting facility

**Thread Size:**

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

21 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Contact Load Current Rating:**

0.1 amperes resistive load dc at sea level

**Contact Arrangement Truth Table:**

Special each section

**Special Truth Table Identification:**

91812-code b 21 each section

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unf 2nd mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0