

View Online at <https://aerobasegroup.com/nsn/5930-01-245-9532>

Overall Length:

5.000 inches

Overall Height:

7.000 inches

Overall Width:

7.000 inches

Unthreaded Mounting Hole Diameter:

0.380 inches single mounting facility

Individual Section Quantity:

3

End Application:

Ticonderoga class cg (47); submarine auxillary and miscellaneous systems; nimitz class cvn; systems, jp-5 aviation fuels; sturgeon class ssn (637); gun fire control system, mk 68; los angeles class ssn (688); virginia class cgn (41); spruance class dd (963); forrestal class cv

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section periphery

Throw Quantity:

1 single section periphery

Mounting Facility Circle Radius:

3.310 inches single mounting facility

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Special Features:

Submersible; weapon system essential

Style Designator:

Circular wafer, panel mount

Test Data Document:

81349-mil-s-15743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-15743/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0