## NSN 5930-01-245-9545

Push Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-01-245-9545

Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.430 inches
Overall Height:
1.250 inches
Overall Width:
0.990 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Length:
1.000 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.750 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Green single actuator and amber single actuator
Actuator Inscription:
Start, mot on single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator green; lower half of actuator amber
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.160 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and horizontal split lens
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

## NSN 5930-01-245-9545

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

## **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0