NSN 5930-01-245-9546

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-245-9546

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.430 inches
Overall Height:
1.250 inches
Overall Width:
0.990 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Length:
1.000 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.750 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Red single actuator and amber single actuator
Actuator Inscription:
Stop, mot off pwr avail single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator red; lower half of actuator amber
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.160 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and horizontal split lens
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

NSN 5930-01-245-9546

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0