NSN 5930-01-245-9700

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

Body Style:Panel mounted

Overall Length: 3.706 inches Overall Height: 0.760 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5930-01-245-9700

0.760 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator
Illuminated Actuator Color:
Green single actuator and green single actuator
Actuator Inscription:
Man auto single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
3.606 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Holding mechanism and horizontal split lens and rfi shielding
Nonpile-up Contact Arrangement:
3 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit

NSN 5930-01-245-9700

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Special Features:

T-1 lamp buld size

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0