NSN 5930-01-246-3589

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-246-3589

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof and oiltight
Overall Length: 4.844 inches
Overall Height: 2.109 inches
Overall Width:
1.531 inches
Actuator Style:
Round
Actuator Diameter:
0.625 inches
Actuator Free Position Height:
1.453 inches
Housing Height:
1.781 inches
Housing Length:
4.844 inches
Housing Width:
1.531 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
56.0 inch-ounces
Actuator Movement:
8.0 differential degrees and 16.5 pretravel degrees
Contact Load Current Rating At Maximum Rated Voltage:
100.000 milliamperes resistive dc and 1.200 amperes resistive ac
Precious Material And Location:
Contacts silver

4 screw

Terminal Type And Quantity:

NSN 5930-01-246-3589

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0