NSN 5930-01-247-1224

Push Switch - Page 1 of 2

Test Data Document:



View Online at https://aerobasegroup.com/nsn/5930-01-247-1224

view Offilite at https://aerobasegroup.com/hsi//0900-01-247-1224
Body Style:
Panel mounted
Overall Length:
1.330 inches
Overall Height:
0.740 inches
Overall Width:
0.740 inches
Body Width:
0.740 inches
Body Height:
0.740 inches
Actuator Length:
0.630 inches
Actuator Style:
Rectangular
Actuator Height:
0.160 inches
Actuator Width:
0.630 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
0.980 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc
Special Features:
When illuminated letters appear in yellow

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5930-01-247-1224

Push Switch - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

3 wire loop and 9 turret

Specification Data:

81349-mil-s-22885/100 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0