## NSN 5930-01-247-3045

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-247-3045
Body Style:
Panel mounted
Overall Length:
1.330 inches
Overall Height:
0.740 inches
Overall Width:
0.740 inches
Body Width:
0.740 inches
Body Height:
0.740 inches
Actuator Length:
0.630 inches
Actuator Style:
Rectangular
Actuator Height:
0.160 inches
Actuator Width:
0.630 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
0.980 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc
Special Features:
When illuminated letters appear in red
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 wire loop and 9 turret

## NSN 5930-01-247-3045

Push Switch - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-s-22885/100 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0