## NSN 5930-01-247-3875

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-247-3875

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight and corrosion resistant
Switch Actuator Quantity:
1
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Height:
1.270 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
1.750 inches
Housing Length:
4.200 inches
Housing Width:
1.620 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.340 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.160 inches
Maximum Voltage Rating In Volts:
240.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, one position momentary single switch unit
Actuator Movement:
Between 15.0 pretravel degrees and 60.0 overtravel degrees and 5.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
0.400 amperes resistive dc and 0.200 amperes inductive dc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

No

## NSN 5930-01-247-3875

Sensitive Switch - Page 2 of 2



Fiig:

A053a0