

View Online at <https://aerobasegroup.com/nsn/5930-01-247-4621>

**Thread Class:**

2a single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.437 inches single actuator

**Individual Section Quantity:**

5

**End Application:**

Test set, aviator's night vision imaging system ts-3895/uv

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, flatted single actuator

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

1.25 amperes resistive load dc at sea level and 0.25 amperes inductive load dc at sea level

**Special Features:**

Wired iaw dwg 5003344

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0