

View Online at <https://aerobasegroup.com/nsn/5930-01-247-4621>

Thread Class:

2a single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Individual Section Quantity:

5

End Application:

Test set, aviator's night vision imaging system ts-3895/uv

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

1.25 amperes resistive load dc at sea level and 0.25 amperes inductive load dc at sea level

Special Features:

Wired iaw dwg 5003344

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0