

View Online at <https://aerobasegroup.com/nsn/5930-01-247-4646>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.187 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Corrosion resistant and dustproof and moisture proof

**Overall Length:**

1.694 inches

**Overall Height:**

0.775 inches

**Overall Width:**

0.775 inches

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.094 inches single actuator

**Shaft Diameter:**

0.123 inches single actuator and 0.126 inches single actuator

**Shaft Length:**

0.547 inches single actuator

**Nonturn Device Radius:**

0.312 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 3:00 o'clock

**Operating Temperature Range:**

-55.0/+95.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

20 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

20 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Pin

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

18.0 degrees single actuator

**Detent Rotational Torque Range:**

+8.000/+36.000 inch-ounces single actuator

**Contact Load Current Rating:**

3.0 amperes resistive load dc at sea level

**Special Features:**

Emi grounded

**Style Designator:**

Rectangular panel mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0