

View Online at <https://aerobasegroup.com/nsn/5930-01-247-5372>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.250 inches

**Actuator Free Position Height:**

0.875 inches

**Housing Diameter:**

Between 0.625 inches and 0.720 inches

**Housing Length:**

1.000 inches

**Housing Bushing Length:**

0.625 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

64.0 ounces

**Actuator Movement:**

0.030 differential inches and 0.050 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 4.000 amperes motor dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac and 1.000 amperes lamp ac and 1.000 amperes motor ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0