

View Online at <https://aerobasegroup.com/nsn/5930-01-247-5372>

Thread Class:

2a

Body Style:

Bushing mounted

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.250 inches

Actuator Free Position Height:

0.875 inches

Housing Diameter:

Between 0.625 inches and 0.720 inches

Housing Length:

1.000 inches

Housing Bushing Length:

0.625 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

64.0 ounces

Actuator Movement:

0.030 differential inches and 0.050 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 4.000 amperes motor dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac and 1.000 amperes lamp ac and 1.000 amperes motor ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0