

View Online at <https://aerobasegroup.com/nsn/5930-01-247-5968>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

0.740 inches

Overall Height:

0.890 inches

Overall Width:

0.740 inches

Body Length:

0.680 inches

Body Width:

0.680 inches

Body Height:

0.980 inches

Case Material:

Metal

Actuator Length:

0.630 inches

Actuator Style:

Rectangular

Actuator Height:

0.160 inches

Actuator Width:

0.630 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc

Special Features:

Legend letters show amber when illuminated

Precious Material And Location:

Contacts silver

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 wire loop and 8 turret

Specification Data:

81349-mil-s-22885/100 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0