NSN 5930-01-247-8412

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style: Panel mount



View Online at https://aerobasegroup.com/nsn/5930-01-247-8412

Moisture proof and shock proof
Overall Length:
0.740 inches
Overall Height:
2.960 inches
Overall Width:
0.740 inches
Body Length:
0.740 inches
Body Width:
0.740 inches
Body Height:
2.960 inches
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Red single actuator and red single actuator
Actuator Inscription:
Auto, manual single actuator
Illuminated Actuator Color Sequence:
Top half of actuator red bottom half of actuator red
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Horizontally split screen, in addition there is an extra long reference number which is 8008a1c2d4j3l2m1n (rr) 16auto/manual

NSN 5930-01-247-8412

Push Switch - Page 2 of 2



Terminal Type And Quantity:

18 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0