NSN 5930-01-247-9176

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-247-9176

| Thread Class: | | |
|---|--|--|
| 2b single mounting facility | | |
| Hazardous Locations/environmental Protection: | | |
| Corrosion resistant | | |
| Overall Length: | | |
| 3.625 inches | | |
| Overall Height: | | |
| 1.935 inches | | |
| Overall Width: | | |
| 1.935 inches | | |
| Shaft Diameter: | | |
| 0.250 inches single actuator | | |
| Shaft Length: | | |
| 1.125 inches single actuator | | |
| Individual Section Quantity: | | |
| 6 | | |
| Switch Contact Basic Design: | | |
| Nonpile-up nonsymmetrical | | |
| Mounting Facility Circle Radius: | | |
| 1.156 inches single mounting facility | | |
| Mounting Method: | | |
| Bracket single mounting facility and threaded hole single mounting facility | | |
| Features Provided: | | |
| Actuator knob | | |
| Thready Qty Per Inch (tpi): | | |
| 24 single mounting facility | | |
| Thread Size: | | |
| 0.190 inches single mounting facility | | |
| Contact Voltage Rating In Volts: | | |
| 120.0 dc at sea level | | |
| Mounting Facility Pattern: | | |
| Four position circular single mounting facility | | |
| Switch Actuator Indexing Position Quantity: | | |
| 4 single actuator | | |
| Shaft Type: | | |
| Round, threaded hole single actuator | | |
| Terminal Type: | | |
| Tab w/screw | | |
| Switch Actuator Positioning Increment: | | |

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

NSN 5930-01-247-9176

Rotary Switch - Page 2 of 2



| Style | Desig | nator: |
|-------|-------|--------|
| | | |

Tap, circuit selector

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Specification Data:

81349-mil-s-15291/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0