NSN 5930-01-247-9176

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-247-9176

Thread Class:		
2b single mounting facility		
Hazardous Locations/environmental Protection:		
Corrosion resistant		
Overall Length:		
3.625 inches		
Overall Height:		
1.935 inches		
Overall Width:		
1.935 inches		
Shaft Diameter:		
0.250 inches single actuator		
Shaft Length:		
1.125 inches single actuator		
Individual Section Quantity:		
6		
Switch Contact Basic Design:		
Nonpile-up nonsymmetrical		
Mounting Facility Circle Radius:		
1.156 inches single mounting facility		
Mounting Method:		
Bracket single mounting facility and threaded hole single mounting facility		
Features Provided:		
Actuator knob		
Thready Qty Per Inch (tpi):		
24 single mounting facility		
Thread Size:		
0.190 inches single mounting facility		
Contact Voltage Rating In Volts:		
120.0 dc at sea level		
Mounting Facility Pattern:		
Four position circular single mounting facility		
Switch Actuator Indexing Position Quantity:		
4 single actuator		
Shaft Type:		
Round, threaded hole single actuator		
Terminal Type:		
Tab w/screw		
Switch Actuator Positioning Increment:		

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

NSN 5930-01-247-9176

Rotary Switch - Page 2 of 2



Style	Desig	nator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Specification Data:

81349-mil-s-15291/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0