

View Online at <https://aerobasegroup.com/nsn/5930-01-247-9437>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

7.750 inches

Overall Height:

6.531 inches

Overall Width:

4.937 inches

Unthreaded Mounting Hole Diameter:

0.343 inches

Longest Horizontal Distance Between Mounting Centers:

4.000 inches

Longest Vertical Distance Between Mounting Centers:

4.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

60.00 pounds per square inch gage

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes inductive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.66/+18.00 actuation point pounds per square inch gage and +0.40/+17.74 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0