

View Online at <https://aerobasegroup.com/nsn/5930-01-247-9437>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

7.750 inches

**Overall Height:**

6.531 inches

**Overall Width:**

4.937 inches

**Unthreaded Mounting Hole Diameter:**

0.343 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.000 inches

**Longest Vertical Distance Between Mounting Centers:**

4.000 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

60.00 pounds per square inch gage

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

10.0 amperes inductive load second voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+0.66/+18.00 actuation point pounds per square inch gage and +0.40/+17.74 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

480.0 ac at sea level third voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/mounting lugs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0