NSN 5930-01-247-9442

Sensitive Switch - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5930-01-247-9442 |
|---|
| Hazardous Locations/environmental Protection: |
| Raintight |
| Housing Height: |
| 5.188 inches |
| Housing Width: |
| 3.438 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 4.125 inches |
| Maximum Voltage Rating In Volts: |
| 480.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Actuator Movement: |
| 2.0 pretravel degrees and 55.0 overtravel degrees and 1.0 differential degrees |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 250.000 milliamperes resistive dc and 15.000 amperes resistive ac |
| Special Features: |
| Direct coupled (double flatted shaft) |
| Terminal Type And Quantity: |
| 6 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |
| |
| |
| |
| |