

View Online at <https://aerobasegroup.com/nsn/5930-01-248-3345>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

1.680 inches

**Overall Height:**

0.875 inches

**Overall Width:**

0.875 inches

**Bushing Length:**

0.312 inches

**Body Length:**

0.806 inches

**Body Width:**

0.500 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.375 inches

**Actuator Height:**

0.250 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Rfi shielding and actuator seal

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc

**Precious Material And Location:**

Contact surfaces gold or contacts silver

**Unable To Decode:**

Unable to decode or unable to decode

**Thread Series Designator:**

Unf

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0