

View Online at <https://aerobasegroup.com/nsn/5930-01-248-7170>

**Body Style:**

Panel mounted

**Overall Length:**

2.510 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.750 inches

**Body Width:**

0.750 inches

**Body Height:**

0.750 inches

**Actuator Length:**

0.658 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.180 inches

**Actuator Width:**

0.658 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Yellow single actuator

**Actuator Inscription:**

Push to reset single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Aircraft, awacs, d-3a

**Mounting Surface To Terminal End Distance:**

2.330 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:**

Weapon system essential

**Test Data Document:**

81349-mil-prf-22885/83 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

5 tab, solder lug and 3 turret

**Specification Data:**

81349-mil-prf-22885/83 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A053a0

**Mil-std (military Standard):**

Mil-prf-22885 spec.