NSN 5930-01-249-1945

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-249-1945

Thread Class:
2b all threaded hole
Overall Length:
3.062 inches
Overall Width:
1.438 inches
Body Diameter:
0.500 inches
Distance Between Mounting Facility Centers:
0.750 inches
Tempurature Sensing Element Type:
Expanding shell
Mounting Method:
Bracket and threaded hole
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.138 inches all threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Terminal Type: Tab, solder lug
• •
Tab, solder lug
Tab, solder lug Contact Load Current Rating:
Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load first voltage
Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load first voltage Contact Adjustability:
Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable
Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating:
Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 140.00 actuation point degrees fahrenheit
Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 140.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts:
Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 140.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 32.0 dc at sea level second voltage
Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 140.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 32.0 dc at sea level second voltage Media For Which Designed:
Tab, solder lug Contact Load Current Rating: 5.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable Contact Stimulus Rating: 140.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 32.0 dc at sea level second voltage Media For Which Designed: Gas or liquid

N/a

NSN 5930-01-249-1945

Thermostatic Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A048b0