

View Online at <https://aerobasegroup.com/nsn/5930-01-249-1995>

**Hazardous Locations/environmental Protection:**

Weather resistant

**Overall Length:**

4.703 inches

**Overall Height:**

4.453 inches

**Overall Width:**

2.938 inches

**Body Height:**

4.078 inches

**Unthreaded Mounting Hole Diameter:**

0.297 inches

**Capillary Tube Length:**

300.0 inches

**Bulb Length:**

4.000 inches

**Bulb Diameter:**

0.875 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.750 inches

**Longest Vertical Distance Between Mounting Centers:**

3.125 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally closed, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load third voltage

**Contact Adjustability:**

Actuation point adjustable, preset and deactuation point adjustable, preset

**Contact Adjustment Range:**

-10.00/+65.00 actuation point degrees fahrenheit and -10.00/+65.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External actuation point screw and external deactuation point screw

**Contact Stimulus Rating:**

25.00 actuation point degrees fahrenheit and 35.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

240.0 dc at sea level third voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0