

View Online at <https://aerobasegroup.com/nsn/5930-01-249-1995>

Hazardous Locations/environmental Protection:

Weather resistant

Overall Length:

4.703 inches

Overall Height:

4.453 inches

Overall Width:

2.938 inches

Body Height:

4.078 inches

Unthreaded Mounting Hole Diameter:

0.297 inches

Capillary Tube Length:

300.0 inches

Bulb Length:

4.000 inches

Bulb Diameter:

0.875 inches

Longest Horizontal Distance Between Mounting Centers:

2.750 inches

Longest Vertical Distance Between Mounting Centers:

3.125 inches

Tempurature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

-10.00/+65.00 actuation point degrees fahrenheit and -10.00/+65.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Stimulus Rating:

25.00 actuation point degrees fahrenheit and 35.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

240.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0