

View Online at <https://aerobasegroup.com/nsn/5930-01-249-4800>

Hazardous Locations/environmental Protection:

Explosion proof and raintight and weathertight

Overall Length:

5.562 inches

Overall Height:

5.250 inches

Body Diameter:

5.062 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Capillary Tube Length:

72.0 inches

Bulb Length:

2.594 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

3.625 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

400.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+30.00/+250.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point knob and external actuation point dial

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/port

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0