

View Online at <https://aerobasegroup.com/nsn/5930-01-249-4801>

**Overall Width:**

4.220 inches

**Mounting Slot Width:**

0.220 inches single mounting facility

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

4.500 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.120 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility and slot single mounting facility

**Features Provided:**

Actuator knob and cam actuated and legend plate and spring return

**Contact Voltage Rating In Volts:**

600.0 highest dc voltage rating at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Cam Actuated Switch Contact Arrangement:**

2 pole, single throw, normally open, double make, momentary action each switch each section in-line

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Terminal Type:**

Screw

**Contact Load Current Rating:**

6.0 amperes resistive load lowest ac voltage rating at sea level

**Special Features:**

Special enclosure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0