

View Online at <https://aerobasegroup.com/nsn/5930-01-249-4813>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Moisture proof and dustproof and shock resistant

**Overall Height:**

0.875 inches

**Overall Width:**

0.875 inches

**Bushing Length:**

0.375 inches

**Case Material:**

Metal

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0