## NSN 5930-01-249-5917

Flow Switch - Page 1 of 1

A048b0



View Online at https://aerobasegroup.com/nsn/5930-01-249-5917 **Overall Length:** 10.782 inches **Overall Height:** 3.812 inches **Overall Width: 4.375** inches **Unthreaded Mounting Hole Diameter:** 0.188 inches **Longest Horizontal Distance Between Mounting Centers:** 3.812 inches **Longest Vertical Distance Between Mounting Centers: 3.188** inches **Mounting Method:** Flange and unthreaded hole **Features Provided:** Electrical access port **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Four position rectangular **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Contact Load Current Rating:** 15.0 amperes resistive load second voltage and 3.7 amperes motor load second voltage **Contact Adjustability:** Actuation point adjustable and deactuation point adjustable **Contact Adjustment Range:** +235.00/+1470.00 actuation point feet per minute and +175.00/+1395.00 deactuation point feet per minute **Contact Voltage Rating In Volts:** 230.0 ac at sea level second voltage Media For Which Designed: Gas Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: