## NSN 5930-01-249-7579

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-249-7579
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Length:
3.250 inches
Overall Height:
3.000 inches
Overall Width:
3.000 inches
Individual Section Quantity:
4
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
02000-1
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Facility Circle Radius:
1.156 inches single mounting facility
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
350.0 highest dc voltage rating at sea level
Switch Actuator Momentary Position:
Clockwise single actuator
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:

**Contact Switching Action:** 

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

## NSN 5930-01-249-7579

Rotary Switch - Page 2 of 2



Switch Actuator Stop Dev	/ice i	ype:
--------------------------	--------	------

Fixed stop single actuator

## **Contact Load Current Rating:**

10.0 amperes resistive load lowest dc voltage rating at sea level and 10.0 amperes inductive load lowest dc voltage rating at sea level

**Style Designator:** 

Tap, circuit selector

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0