NSN 5930-01-249-7581

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-249-7581 **Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Shock resistant and vibration resistant **Overall Length:** 6.000 inches **Overall Height:** 3.750 inches **Overall Width:** 3.750 inches **Individual Section Quantity:** 4 **Knob Manufacturer Code:** 82121 **Knob Manufacturer Part Number:** 02000-4-1 **Longest Horizontal Distance Between Mounting Centers:** 2.300 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.300 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 8 single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

NSN 5930-01-249-7581

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0