NSN 5930-01-249-7583

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mounted

Shock resistant

Overall Length:
3.380 inches

Overall Height:



View Online at https://aerobasegroup.com/nsn/5930-01-249-7583

0.750 inches
Overall Width:
0.750 inches
Body Width:
0.679 inches
Body Height:
0.750 inches
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.430 inches
Actuator Width:
0.740 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Natural single actuator and green single actuator
Actuator Inscription:
Assign, achieved single actuator
Illuminated Actuator Color Sequence:
Top half of actuator clear bottom half of actuator green
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and holding mechanism and horizontal split lens
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, both positions maintained single switch unit

NSN 5930-01-249-7583

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0