

View Online at <https://aerobasegroup.com/nsn/5930-01-249-8205>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

2.510 inches

**First Flat Length:**

0.440 inches single actuator

**Flat Height:**

0.211 inches single actuator and 0.221 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.505 inches single actuator

**Overall Diameter:**

1.180 inches

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

4 each section front

**Throw Quantity:**

2 each section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Features Provided:**

Rfi shielding

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Rotor Through Connection Quantity:**

4 each section

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

6.0 amperes resistive load dc at sea level and 3.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0