## NSN 5930-01-249-8286

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-249-8286

Thr	ead	CI	ass:

2b single mounting facility

## **Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:** 

9.988 inches

**Overall Height:** 

3.750 inches

**Overall Width:** 

3.750 inches

**Individual Section Quantity:** 

14

**Knob Manufacturer Code:** 

82121

**Knob Manufacturer Part Number:** 

02000-4-1

**Longest Horizontal Distance Between Mounting Centers:** 

2.297 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

2.297 inches single mounting facility

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

30.0 dc at sea level

**Mounting Facility Pattern:** 

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

8 single actuator

**Terminal Type:** 

Tab w/screw

**Contact Switching Action:** 

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

## NSN 5930-01-249-8286

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

10.0 amperes resistive load dc at sea level

**Precious Material And Location:** 

Contact surfaces silver

**Precious Material:** 

Silver

Style Designator:

Tap, circuit selector

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0