

View Online at <https://aerobasegroup.com/nsn/5930-01-249-8287>

Thread Class:

2a 1st mounting facility

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

12.158 inches

Overall Height:

2.810 inches

Overall Width:

2.810 inches

Unthreaded Mounting Hole Diameter:

0.213 inches 2nd mounting facility

Individual Section Quantity:

20

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

02000-4-1

Longest Horizontal Distance Between Mounting Centers:

2.300 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

2.300 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

0.905 inches 1st mounting facility

Mounting Method:

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

Features Provided:

Actuator knob and dummy section

Thread Size:

0.190 inches 1st mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0