

View Online at <https://aerobasegroup.com/nsn/5930-01-249-8287>

**Thread Class:**

2a 1st mounting facility

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

12.158 inches

**Overall Height:**

2.810 inches

**Overall Width:**

2.810 inches

**Unthreaded Mounting Hole Diameter:**

0.213 inches 2nd mounting facility

**Individual Section Quantity:**

20

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

02000-4-1

**Longest Horizontal Distance Between Mounting Centers:**

2.300 inches 2nd mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.300 inches 2nd mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:**

0.905 inches 1st mounting facility

**Mounting Method:**

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

**Features Provided:**

Actuator knob and dummy section

**Thread Size:**

0.190 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0