NSN 5930-01-249-8288

Rotary Switch Section - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-249-8288

| Overall Height: |
|--|
| 2.531 inches |
| Overall Width: |
| 1.625 inches |
| Body Thickness: |
| 0.062 inches |
| Distance Between Mounting Facility Centers: |
| 1.562 inches single mounting facility |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 2 single section front |
| Throw Quantity: |
| 4 single section front |
| Mounting Method: |
| Strut single mounting facility |
| Contact Voltage Rating In Volts: |
| 30.0 dc at sea level |
| Mounting Facility Pattern: |
| Two position in-line single mounting facility |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Makes before breaks single section rear |
| Contact Load Current Rating: |
| 500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level |
| Special Features: |
| Jumpers wired iaw dwg 269-2052-020 |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Switch section, rotary |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No. |

No

NSN 5930-01-249-8288

Rotary Switch Section - Page 2 of 2



Fiig:

A052b0