

View Online at <https://aerobasegroup.com/nsn/5930-01-249-9105>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.310 inches single mounting facility

**Overall Length:**

2.230 inches

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.540 inches single actuator

**Overall Diameter:**

0.750 inches

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**End Application:**

5895-01-057-6262 radio data link, sound ranging an/gra-114

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

10 each section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level and 125.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0