NSN 5930-01-249-9110

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-249-9110

Body Style:
Hole mounted
Overall Length:
2.467 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.375 inches
Overall Width:
0.690 inches
Body Length:
1.940 inches
Body Width:
0.690 inches
Body Height:
0.830 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.125 inches
Actuator Roller Diameter:
0.370 inches
Actuator Roller Width:
0.160 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
0.5 ounces
Switch Actuating Force:
5.0 ounces
Actuator Movement:
0.156 pretravel inches and 0.062 overtravel inches and 0.050 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

NSN 5930-01-249-9110

Sensitive Switch - Page 2 of 2



Terminal Type	And	Quantity:
---------------	-----	-----------

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0