NSN 5930-01-249-9691

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-249-9691

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.123 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.190 inches

Individual Section Quantity:

···

Nonturn Device Type:

Slotted bushing at 4: 30 o'clock

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

End Application:

Combat control acoustic an/bsy-1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

17 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

17 single actuator

NSN 5930-01-249-9691

Rotary Switch - Page 2 of 2

A052b0



Shaft Type:	
Round, flatted single actuator	
Terminal Type:	
Tab, solder lug	
Contact Switching Action:	
Breaks before makes each section rear	
Switch Actuator Positioning Increment:	
18.0 degrees single actuator	
Contact Load Current Rating:	
50.0 milliamperes resistive load dc at altitude and 10.0 milliamperes inductive load dc at altitude	
Style Designator:	
Tap, circular, bushing mount	
Test Data Document:	
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	n
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unef single mounting facility	
Specification Data:	
81349-mil-s-3786/36 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	