

View Online at <https://aerobasegroup.com/nsn/5930-01-250-0440>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.800 inches

Overall Height:

2.795 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Free Position Height:

1.795 inches

Housing Height:

2.000 inches

Housing Length:

2.800 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.000 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

Between 28.0 ounces and 54.0 ounces

Actuator Movement:

0.050 pretravel inches and 0.218 overtravel inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 15.000 amperes resistive ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 screw

Specification Data:

81349-mil-s-8805/62 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0