NSN 5930-01-250-1541

Thermostatic Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-250-1541

He will be a few of a few or and Burtonia
Hazardous Locations/environmental Protection:
Dustproof and rainproof and waterproof
Capillary Tube Length:
120.0 inches
Bulb Length:
2.500 inches
Bulb Diameter:
0.290 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Contact Load Current Rating:
16.0 amperes resistive load single voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
-15.00/+65.00 actuation point degrees celsius and -15.00/+65.00 deactuation point degrees celsius
Contact Adjustment Type:
External actuation point knob with scale and external deactuation point knob with scale
Contact Voltage Rating In Volts:
12.0 ac at sea level single voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A048b0