

View Online at <https://aerobasegroup.com/nsn/5930-01-250-5904>

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

3.000 inches

**Overall Height:**

2.235 inches

**Overall Width:**

2.100 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.740 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.200 inches single mounting facility

**Operating Temperature Range:**

-65.0/+55.0 degrees celsius

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel single actuator

**Features Provided:**

Illuminated

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

7off, sigma symbol + delta symbol 1, sigma symbol + delta symbol 2, sigma symbol - delta symbol 1, sigma symbol - delta symbol 2, off, sigma symbol + delta symbol 1, sigma symbol + delta symbol 2, sigma symbol - delta symbol 1, sigma symbol - delta symbol 2 single section

**Contact Arrangement Truth Table:**

Decimal, 1 pole - 10 positions single section

**Color:**

White single indicator marking

**Precious Material And Location:**

Printed circuit board circuit surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0