## NSN 5930-01-250-7511

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-250-7511

Padu Stula
Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.890 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.094 inches
Actuator Height:
0.330 inches
Actuator Free Position Height:
0.660 inches
Maximum Voltage Rating In Volts:
250.0 ac
End Application:
Switch assembly-temp, c110-102w, catalog number 9174-100 used aboard wmec 270 ft b class coast guard vessels
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
2.0 ounces
Switch Actuating Force:
14.0 ounces
Actuator Movement:
Between 0.020 pretravel inches and 0.005 overtravel inches and 0.001 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac
Terminal Type And Quantity:
3 tab w/screw
Shelf Life:

N/a

## NSN 5930-01-250-7511

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0