

View Online at <https://aerobasegroup.com/nsn/5930-01-251-3502>

Hazardous Locations/environmental Protection:

Shock proof and watertight

Overall Length:

3.680 inches

Overall Height:

6.250 inches

Overall Width:

3.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

3.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

5.500 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Flange single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and illuminated and legend plate

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

750.0 milliamperes inductive load highest ac voltage rating at sea level

Special Features:

Legend plate reads door dogged, normal, emer stop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0